

Easy CramBible Lab



1Y0-A11

Citrix Basic Administration for Citrix NetScaler 9.0

**** Single-user License ****

This copy can be only used by yourself for educational purposes

Web: <http://www.crambible.com/>

E-mail: web@crambible.com

Important Note
Please Read Carefully**Study Tips**

This product will provide you questions and answers along with carefully compiled and written by our experts. Try to understand the concepts behind the questions instead of cramming the questions.

Go through the entire document at least twice so that you make sure that you are not missing anything.

Latest Version

We are constantly reviewing our products. New material is added and old material is revised. Free updates are available for 90 days after the purchase. You should check your member zone at CramBible an update 3-4 days before the scheduled exam date.

Here is the procedure to get the latest version:

1. Go to www.CramBible.com
2. Click on Member zone/Log in
3. The latest versions of all purchased products are download from here. Just click the links.

For most updates, it is enough just to print the new questions at the end of the new version, not the whole document.

Feedback

Feedback on specific questions should be send to web@CramBible.com. You should state: Exam number and version, question number, and login ID.

Our experts will answer your mail promptly.

Copyright

Each pdf file contains a unique serial number associated with your particular name and contact information for security purposes. So if we find out that a particular pdf file is being distributed by you, CramBible reserves the right to take legal action against you according to the International Copyright Laws.

THE TOTAL NUMBER OF QUESTIONS IS 114

QUESTION NO: 1 An administrator should configure Link Aggregation on a 7000 NetScaler system when _____. (Choose the correct option to complete the sentence.)

- A. redundancy on a half duplex operation is required
- B. redundancy on an operation across multiple data rates is required
- C. the bandwidth requirements inbound to or outbound from the Netscaler are greater than 1 Gb/sec
- D. the bandwidth requirements inbound to or outbound from the Netscaler are greater than 8 Gb/sec

Answer: C

QUESTION NO: 2 Scenario: An administrator must set up a NetScaler system network with USIP mode enabled. The NetScaler must be able to preserve client IP addresses in TCP/IP packets reaching the back-end servers except for connections coming from particular IP addresses that are defined in an ACL. In the case of connections coming from the IP addresses defined in the ACL, the packets reaching the back-end servers should receive the NetScaler IP address instead of the client IP address. On which entity should RNAT be configured to meet the requirements in this scenario according to best practices?

- A. ACL
- B. Client
- C. Virtual server
- D. Back-end server

Answer: A

QUESTION NO: 3 How can an administrator configure a health check for a server receiving HTTP traffic so that it monitors the responses of the server to actual client requests as opposed to probes whenever possible?

- A. Use the default TCP monitor
- B. Configure an HTTP-ECV monitor
- C. Configure an HTTP-Inline monitor
- D. Use the TCP monitor with the transparent parameter selected
- E. Configure an HTTP monitor with the transparent parameter selected

Answer: C

QUESTION NO: 4 An administrator configured cache redirection and needs to provide a report of how that feature is functioning in the network environment. What can the administrator use to see a graphical representation of the statistics for the vserver performing the cache redirection?

- A. The monitor view for the service bound to the correct vserver
- B. The chart option in the Dashboard once the correct vserver is selected
- C. The chart option in the Dashboard for the service bound to the correct vserver
- D. The request and response rates option in the Dashboard once the correct vserver is selected

Answer: B

QUESTION NO: 5 An administrator has just enabled caching and wants to make sure that this will positively impact server performance. Which information can the administrator get from the Dashboard to determine

whether server performance was positively affected by enabling caching?

- A. Client connection count increases
- B. Server side request rate increases
- C. Client connection count decreases
- D. Server side request rate decreases

Answer: D

QUESTION NO: 6 An SNMP manager attempted to poll for an OID but received the error message: "response timeout."

Which option could the administrator have misconfigured for SNMPv2 to cause this error message?

- A. SNMP trap
- B. SNMP user
- C. SNMP group
- D. SNMP community

Answer: D

QUESTION NO: 7 Which SNMP trap must an administrator configure to be informed when the response time for a monitor probe that had exceeded the set threshold returns to normal?

- A. entityup
- B. entitydown

C. monRespTimeoutAboveThresh

D. monRespTimeoutBelowThresh

Answer: D

QUESTION NO: 8 Scenario: An administrator needs to create a health check that will mark an HTTP service down if the bound monitor probe fails. The administrator wants to create a monitor and configure the health check so that a trap is sent if the monitor probe reply exceeds 20 milliseconds. How can the administrator create the monitor for this health check using the command line interface?

A. set mon monitor-HTTP-1 HTTP -interval 20 milli

B. add lb mon monitor-HTTP-1 HTTP -interval 20 milli

C. set mon monitor-HTTP-1 HTTP -resptimeout 20 milli

D. add lb mon monitor-HTTP-1 HTTP -resptimeout 20 milli

Answer: D

QUESTION NO: 9 Scenario: An administrator is planning on configuring health checks for services bound to web servers 1 and 2 which are listening on TCP port 80 for HTTP and TCP port 443 for HTTPS. Service1 receives the encrypted traffic and Service 2 receives the clear text traffic. How should the administrator create the monitor for Service1 using the command line interface?

A. set mon monitor-SVC1-Mon TCP -secure YES

B. add lb mon monitor-SVC1-Mon HTTP -secure YES

C. set mon monitor-SVC1-Mon HTTP -transparent NO